

CONTROLS

Switches



CS-7 - Three gang switch for fan heater control

For use with	800 Series SCHG RH SMH CA
Settings	On/off/high heat/low heat/fan only (summer use)
Voltage supply	230V
Mounting	Surface
Dimensions	148 x 88 x 45mm
Ingress protection	IP30



CS-2 - Two gang switch for halogen or ceramic heater control

For use with	HN3-30 and CH2-30 (EXCEPT LINEAR MODELS)
Settings	Full heat/ $\frac{1}{2}$ heat
Voltage supply	230V
Mounting	Surface
Dimensions	85 x 85 x 48mm
Ingress protection	IP30



CS-3 - Three gang switch for halogen heater control

For use with	HN3-45 and HN3-60
Settings	Full heat/ $\frac{2}{3}$ heat/ $\frac{1}{3}$ heat
Voltage supply	230V
Mounting	Surface
Dimensions	146 x 85 x 48mm
Ingress protection	IP30



CS-4 - Single gang switch for halogen or ceramic heater control

For use with	HN3-15, HN3-20, HN3-30, CH2-15, CH2-30 (4 kW MAX)
Settings	On/off
Voltage supply	230V
Mounting	Surface
Dimensions	85 x 85 x 48mm
Ingress protection	IP30



CS-5 - Push button

For use with	MC1 halogen heater control box (see page 59) SSR soft start relay (see page 79)
Function	Triggers MC1's or SSR's built-in run-down timer
Voltage supply	230V
Mounting	Surface
Dimensions	85 x 85 x 48mm
Ingress protection	IP30



CS-6 - Six gang switch for multiple halogen or ceramic heater control

For use with	6 x HN3-15 or CH2-15 (settings: on/off) 6 x HN3-20 (settings on/off) 3 x HN3-30 or CH2-30 EXCEPT LINEAR MODELS (settings: 1.5kW/3kW/off) 2 x HN3-45 (settings: 1.5kW/3kW/4.5kW/off) 2 x HN3-60 (settings: 2kW/4kW/6kW/off)
Voltage supply	230V
Mounting	Surface
Dimensions	146mm x 146mm x 48mm
Ingress protection	IP30
Special features	A full set of adhesive labels supplied for all above options Individual switches selected to withstand halogen lamp inrush



CS-8 - Master Switch

For use with	MC1 halogen control box
Function	Switches system on and off – overrides all controls except frost thermostat
Voltage supply	230V
Mounting	Surface
Dimensions	85 x 85 x 48mm
Ingress protection	IP30



OUH2-S Switch for OUH2 industrial fan heater control

For use with	Any heater or group of heaters from the OUH2 range
Settings	On/off/fan only (summer use)
Voltage supply	230V
Mounting	Remote surface mounting or mounted onto an OUH2 heater
Dimensions	85 x 85 x 48mm
Ingress protection	IP30