

NEW



# X50<sup>®</sup>

Wattage and colour selectable  
fire-rated LED downlight

TWO WATTAGE & THREE  
COLOUR SELECTABLE



TWO-PART, DOUBLE  
HINGED CONNECTOR




SIX INTERCHANGEABLE  
BEZEL OPTIONS



## Unique easy access resistance testing terminals\*

Secure plug and play connection, allows for first fix termination. Includes three easy access probe testing terminals for insulation resistance testing.




### Designed to accommodate all testing probe types

The easy access testing terminals have been designed to fit commonly used probe sizes.



# Plug and play two-part connector\*

Double hinged clear casing\* allows for clearer access to terminal blocks, whilst a clear cover provides reassurance of secure termination.




## Secure lever terminal block

Ultra secure lever terminals maintain a secure connection, and have been TUV tested to EN 61984:2009 to ensure a strong hold. Accommodates solid & stranded cable.

# Easy glide protective clips\*

The easy glide protective clips on X50® are designed to reduce ceiling damage and allow for simple ceiling access.



## Wattage & colour selectable from below the ceiling

Adjust the Wattage and colour temperature via a simple switch. Choose between 3.5W or 5W, and 3000K/4000K/5700K colour temperatures. Up to 140 lumens per circuit Watt.

# X50<sup>®</sup>

NEW

- Two wattage and three colour selectable from beneath the ceiling
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings\*\*
- Available in a multipack of 10 with white bezel (JC1101/WH10) or without bezel (JC1101/NB), add bezel with JC1107 (add suffix)

✓ JC1107/WH\*  
(Bezel only)



JC1107/BN\*  
(Bezel only)



JC1107/CH\*  
(Bezel only)



JC1107/BR\*  
(Bezel only)



JC1107/BLK\*  
(Bezel only)



JC1107/ANTH\*  
(Bezel only)



∧ JC1101/WH10 Multipack available



Rating



Class 1



Colour switchable



Wattage switchable



CRI: Ra




Warranty\*



Dimmable



Beam



Cut-out: Ø68-70mm

CODE	DESCRIPTION	COL TEMP.	DIM.	WATT	LUMENS	LPCW
JC1101/WH10	X50 Multipack of 10 with white bezels	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140
JC1101/NB	X50 without bezel	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140
JC1107*	Separate bezel for X50 (add suffix)	-	-	-	-	-
JC131003	X50 Emergency Pack	-	-	-	-	-

\*For Anthracite add /ANTH suffix, Black add /BLK suffix, for Brushed Brass add /BR suffix, for Brushed Nickel add /BN suffix, for Chrome add /CH suffix, for White add /WH suffix.

†Bezel only, to be used with JC1101/NB X50 body (sold separately).

**Body:** Steel. **Lens:** Polycarbonate. **Bezel:** Aluminium.

\*For fast support, register at [jcc.co.uk/warranty](http://jcc.co.uk/warranty), or contact [warranty@jcc.co.uk](mailto:warranty@jcc.co.uk) with your proof of purchase.

\*\*It is the responsibility of the installer to ensure compliance with all relevant regulations. See [jcc.co.uk](http://jcc.co.uk) for full details.

# X50<sup>®</sup> Tilt IP65

**NEW**

- Two wattage and three colour selectable from remote driver
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings\*\*
- 20° tiltable adjustment


✓ JC1102/WH



✓ JC1102/CH



✓ JC1102/BN



CODE	DESCRIPTION	COL TEMP.	DIM.	WATT	LUMENS	LPCW
JC1102/BN	X50 with brushed nickel bezel	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140
JC1102/CH	X50 with chrome bezel	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140
JC1102/WH	X50 with white bezel	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140

**Body:** Steel. **Lens:** Polycarbonate. **Bezel:** Aluminium.

\*For fast support, register at [jcc.co.uk/warranty](http://jcc.co.uk/warranty), or contact [warranty@jcc.co.uk](mailto:warranty@jcc.co.uk) with your proof of purchase.

\*\*It is the responsibility of the installer to ensure compliance with all relevant regulations. See [jcc.co.uk](http://jcc.co.uk) for full details.

# X50® Multipack of 10

NEW

- Two wattage and three colour selectable from beneath the ceiling
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings\*\*

∨ JC1101/WH10



IP 65
Class 1
Colour switchable
Wattage switchable
CRI: Ra 80
5yr Warranty\*
Dimmable
Beam 60°

CODE	DESCRIPTION	COL TEMP.	DIM.	WATT	LUMENS	LPCW
JC1101/WH10	X50 Multipack of 10 with white bezels	3000K/4000K/5700K	Yes	3W/5W	480/700	137/140

Body: Steel. Lens: Polycarbonate. Bezel: Aluminium.

\*For fast support, register at [jcc.co.uk/warranty](http://jcc.co.uk/warranty), or contact [warranty@jcc.co.uk](mailto:warranty@jcc.co.uk) with your proof of purchase.

\*\*It is the responsibility of the installer to ensure compliance with all relevant regulations. See [jcc.co.uk](http://jcc.co.uk) for full details.