## **X**nightsbridge

## **DATASHEET**



## **SN8333W**

45A DP Switch & 13A Socket - White Rockers

www.mlaccessories.co.uk

NET WEIGHT (KG)  FINISH  White  Height - 86 Width - 146 Depth - 36.7 Projection - 15.8 Recessed Depth - 20.9  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  IP RATING  IP20 INPUT VOLTAGE  SWITCH TYPE  Double Pole EARTH TERMINAL  Yes  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MANUFACTURED IN ACCORDANCE WITH  O.202  White  White  Height - 86 Width - 146 Depth - 36.7 Projection - 15.8 Recessed Depth - 20.9  47mm  Construction - Thermoset resin IP20 IP20 IP20 INPUT VOLTAGE  230V 50Hz  SWITCH TYPE  Double Pole  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  45A / 13A  TERMINAL CAPACITY  2 x 6.0mm² or 3 x 4.0mm² ANTI-MICROBIAL PROPERTIES  3rd Party Tested to ISO 22196:2011 WARRANTY  25year(s)  MANUFACTURED IN ACCORDANCE WITH  BS 4177, BS 1363-2 ORIGIN OF MANUFACTURE	MLA PART CODE	SN8333W
FINISH  DIMENSIONS (MM)  DIMENSIONS (MM)  DIMENSIONS (MM)  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  IP RATING  IP 20  INPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MANUFACTURED IN ACCORDANCE WITH  DIMENSIONS (MM)  White  Height - 86 Width - 146 Depth - 280 Width - 146 Depth - 20.9  ANTI-MICROBIAL PROPERTIES  White  Construction - Thermoset resin IP 20  LOAD 1920  EARTH TERMINAL  Yes  LOAD 230V 50Hz  Double Pole  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  45A / 13A  TERMINAL CAPACITY  2 x 6.0mm² or 3 x 4.0mm²  ANTI-MICROBIAL PROPERTIES  3rd Party Tested to ISO 22196:2011  WARRANTY  ESPECIAL  BS 4177, BS 1363-2  ORIGIN OF MANUFACTURE	DESCRIPTION	45A DP Switch & 13A Socket - White Rockers
DIMENSIONS (MM)  Height - 86 Width - 146 Depth - 36.7 Projection - 15.8 Recessed Depth - 20.9  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  Construction - Thermoset resin IP RATING  IP20 INPUT VOLTAGE  SWITCH TYPE  Double Pole EARTH TERMINAL  Yes  LOAD/MAX. LOAD  ATERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MANUFACTURED IN ACCORDANCE WITH  BS 4177, BS 1363-2  ORIGIN OF MANUFACTURE  China	NET WEIGHT (KG)	0.202
DIMENSIONS (MM)  Dimensions (MM)  Width - 146 Depth - 36.7 Projection - 15.8 Recessed Depth - 20.9  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  Construction - Thermoset resin IP RATING  IP20 INPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MANUFACTURED IN ACCORDANCE WITH  DIVID Total Service of the service	FINISH	White
CONSTRUCTION  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MANUFACTURED IN ACCORDANCE WITH  Construction - Thermoset resin  IP20  230V 50Hz  Double Pole  Poss  230V 50Hz  240	DIMENSIONS (MM)	Width - 146 Depth - 36.7 Projection - 15.8
IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 45A / 13A TERMINAL CAPACITY 2 x 6.0mm² or 3 x 4.0mm² ANTI-MICROBIAL PROPERTIES 3rd Party Tested to ISO 22196:2011 WARRANTY 25year(s) MANUFACTURED IN ACCORDANCE WITH BS 4177, BS 1363-2 ORIGIN OF MANUFACTURE China	MINIMUM MOUNTING BOX DEPTH	47mm
INPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  MARNANTY  WARRANTY  MANUFACTURED IN ACCORDANCE WITH  ORIGIN OF MANUFACTURE  230V 50Hz  Double Pole  245A / 13A  2 x 6.0mm² or 3 x 4.0mm²  2 x 6.0mm² or 3 x 4.0mm²  2 x 6.0mm² or 3 x 4.0mm²  2 year(s)  BS 4177, BS 1363-2  China	CONSTRUCTION	Construction - Thermoset resin
SWITCH TYPE  EARTH TERMINAL  LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  WARRANTY  MANUFACTURED IN ACCORDANCE WITH  Double Pole  Yes  45A / 13A  2 x 6.0mm² or 3 x 4.0mm²  3rd Party Tested to ISO 22196:2011  25year(s)  BS 4177, BS 1363-2  China	IP RATING	IP20
EARTH TERMINAL  LOAD/MAX. LOAD  45A / 13A  TERMINAL CAPACITY  2 x 6.0mm² or 3 x 4.0mm²  ANTI-MICROBIAL PROPERTIES  3rd Party Tested to ISO 22196:2011  WARRANTY  25year(s)  MANUFACTURED IN ACCORDANCE WITH  BS 4177, BS 1363-2  China	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD  TERMINAL CAPACITY  ANTI-MICROBIAL PROPERTIES  WARRANTY  MANUFACTURED IN ACCORDANCE WITH  ORIGIN OF MANUFACTURE  A5A / 13A  2 x 6.0mm² or 3 x 4.0mm²  3rd Party Tested to ISO 22196:2011  25year(s)  BS 4177, BS 1363-2  China	SWITCH TYPE	Double Pole
TERMINAL CAPACITY  2 x 6.0mm² or 3 x 4.0mm²  ANTI-MICROBIAL PROPERTIES  3rd Party Tested to ISO 22196:2011  WARRANTY  25year(s)  MANUFACTURED IN ACCORDANCE WITH  BS 4177, BS 1363-2  China	EARTH TERMINAL	Yes
ANTI-MICROBIAL PROPERTIES  3rd Party Tested to ISO 22196:2011  25year(s)  MANUFACTURED IN ACCORDANCE WITH  BS 4177, BS 1363-2  China	LOAD/MAX. LOAD	45A / 13A
WARRANTY 25year(s)  MANUFACTURED IN ACCORDANCE WITH BS 4177, BS 1363-2  ORIGIN OF MANUFACTURE China	TERMINAL CAPACITY	2 x 6.0mm² or 3 x 4.0mm²
MANUFACTURED IN ACCORDANCE WITH BS 4177, BS 1363-2 ORIGIN OF MANUFACTURE China	ANTI-MICROBIAL PROPERTIES	3rd Party Tested to ISO 22196:2011
ORIGIN OF MANUFACTURE China	WARRANTY	25year(s)
	MANUFACTURED IN ACCORDANCE WITH	BS 4177, BS 1363-2
DECLARATION OF CONFORMITY (HELD ON FILE)  Yes	ORIGIN OF MANUFACTURE	China
DESERTATION OF SOME STRUCT (NEED SWITEL)	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
<b>EAN</b> 5056270802061	EAN	5056270802061

Date Created: 27/02/2025 15:55





