## **X**nightsbridge


### **DATASHEET**



#### **BATS6UHL**

### 230V 6ft 100W LED Ultra High Lumen Batten - 4000K

www.mlaccessories.co.uk



MLA PART CODE	BATS6UHL
DESCRIPTION	230V 6ft 100W LED Ultra High Lumen Batten - 4000K
NET WEIGHT (KG)	2
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1790 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	100
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	13500
LUMENS LIGHT SOURCE ONLY (LM)	16120
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	162.05
CIRCUIT WATTAGE (W)	99.54
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.454
DISPLACEMENT FACTOR	>0.9
SVM	0.684
PST-LM	0.033
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000





# **X**nightsbridge

L70B50 LIFESPAN (HRS)	50,000
` '	· ·
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 50W OUTPUT VOLTAGE - 29-43V OUTPUT CURRENT - 1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.64 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811650
WARRANTY  MANUFACTURED IN ACCORDANCE WITH  ORIGIN OF MANUFACTURE  DECLARATION OF CONFORMITY (HELD ON FILE)	OUTPUT CURRENT - 1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.64 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C  5year(s) BS EN 60598 China Yes

Date Created: 07/11/2022 16:55





