Knightsbridge

DATASHEET



M6RCD

13A RCD Fused Spur Unit (Type A) - 30mA

www.mlaccessories.co.uk

MLA PART CODE	M6RCD
DESCRIPTION	13A RCD Fused Spur Unit (Type A) - 30mA
NET WEIGHT (KG)	0.33
FINISH	Powder-coated Silver/Grey
INSERT COLOUR	White
DIMENSIONS (MM)	Height - 81 Width - 81 Projection - 50
CONSTRUCTION	Construction - Premium grade steel Construction 2 - & thermoset resin
CLASS	I
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	2 x 2.5mm ² or 1 x 4.0mm ²
ADDITIONAL FEATURES	RCD trip current of 30mA. Latching type RCD. Cable outlet at front with strain relief.
FUNCTION	RCD trip speed of 30ms
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811568
Date Created: 05/12/2024 14:06	



