

# Electrical PVC Sleeving

2-6mm Diameter

• **Temperature Ranges**

-20°C to +70°C

• **Material:**

PVC.

• **Features:**

Flexible, high-grade PVC sleeving ideal for insulating wire in areas where space is at premium, supplied in continuous coils.  
Self-extinguishing material (30 secs).  
Water, oil and fuel resistant.  
Insulation resistance: 1010 Ohm/cm.  
Dielectric strength: 20kV/mm.  
Elongation at break: 220%.  
Tensile strength: 15MPa.  
Hardness: BSS20-30.  
BS2848/3/85T approved.  
RoHS compliant.



• **Application:**

Used where wires and cables are required to have additional protection and insulation.



# Electrical PVC Sleeving

## 2-6mm Diameter



Item No.	Colour	Length (m)	Internal Diameter (mm)	Wall Thickness (mm)	
SL02X100-PINK	Pink	100	2 (±0.15)	0.50 (±0.10)	
SL03X100-PINK	Pink	100	3 (±0.15)	0.50 (±0.10)	
SL04X100-PINK	Pink	100	4 (±0.15)	0.50 (±0.10)	
SL02X100-BRN	Brown	100	2 (±0.15)	0.50 (±0.10)	
SL03X100-BRN	Brown	100	3 (±0.15)	0.50 (±0.10)	
SL04X100-BRN	Brown	100	4 (±0.15)	0.50 (±0.10)	
SL05X100-BRN	Brown	100	5 (±0.15)	0.50 (±0.10)	
SL06X100-BRN	Brown	100	6 (±0.15)	0.50 (±0.10)	
SL02X100-BLU	Blue	100	2 (±0.15)	0.50 (±0.10)	
SL03X100-BLU	Blue	100	3 (±0.15)	0.50 (±0.10)	
SL04X100-BLU	Blue	100	4 (±0.15)	0.50 (±0.10)	
SL05X100-BLU	Blue	100	5 (±0.15)	0.50 (±0.10)	
SL06X100-BLU	Blue	100	6 (±0.15)	0.50 (±0.10)	
SL02X100-G/Y	Green	Yellow	100	2 (±0.15)	0.50 (±0.10)
SL03X100-G/Y	Green	Yellow	100	3 (±0.15)	0.50 (±0.10)
SL04X100-G/Y	Green	Yellow	100	4 (±0.15)	0.50 (±0.10)
SL05X100-G/Y	Green	Yellow	100	5 (±0.15)	0.50 (±0.10)
SL06X100-G/Y	Green	Yellow	100	6 (±0.15)	0.50 (±0.10)

Internal Diameter (mm)	To cover Cable Size (mm <sup>2</sup> )
2.0	-
3.0	0.5-0.75
4.0	1.5-2.5
5.0	2.5-4.0
6.0	6.0