

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LUTEC

**Supplier's address:** LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

**Model identifier:** 7625601345M

## Type of light source:

|   |         |                                 |      |
|---|---------|---------------------------------|------|
| Lighting technology used:                           | LED     | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Welding |                                 |      |
| Mains or non-mains:                                 | MLS     | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No      | Envelope:                       | -    |
| High luminance light source:                        | No      |                                 |      |
| Anti-glare shield:                                  | No      | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                  | Parameter  | Value                  |
|--|------------------------|--|------------------------|
| <b>General product parameters:</b>   |                        |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 16                     | Energy efficiency class  | E                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 750 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 5 000                  |
| On-mode power ( $P_{on}$ ), expressed in W   | 15,4                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                     |
| Outer dimensions without   | Height                 | Spectral power distribution in the   | See image in last page |
|  | Width                  |  |                        |
|  | Depth                  |  |                        |

|   |       |                                       |                                      |  |
|---|-------|---------------------------------------|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |       |                                       | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>  | Yes   | If yes, equivalent power (W)          | 112                                  |  |
|   |       | Chromaticity coordinates (x and y)    | 0,346<br>0,359                       |  |
| <b>Parameters for LED and OLED light sources:</b>   |       |                                       |                                      |  |
| R9 colour rendering index value   | 24    | Survival factor                       | 1,00                                 |  |
| the lumen maintenance factor  | 0,96  |                                       |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |       |                                       |                                      |  |
| displacement factor (cos $\phi_1$ )   | 0,70  | Colour consistency in McAdam ellipses | 6                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | ..(b) | If yes then replacement claim (W)     | -                                    |  |
| Flicker metric (Pst LM)   | 1,0   | Stroboscopic effect metric (SVM)      | 1,0                                  |  |

(a) : not applicable;

(b) : not applicable;

