DS3HDN

3 Wire Connection IP65 Time Delay Switch

Features & Benefits

- IP65 weatherproof rating
- Light ON times selectable from 2 minutes to 3 hours via 3 position DIL switch
- Blue LED flashes 1 minute before end time as prompt to user
- 3 wire connection neutral required



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount (3 Wire)
Earth Class Rating	Class I
Operating Temperature	-10°C to +40°C
Ingress Protection Rating	IP65
Connection	3-Wire
Push Buttons	Push To Make
Switch Type	Single Pole
Standby Consumption	<0.8W
Number Of Channels	1
Switch Rating	16A Resistive 4A Inductive, Low Voltage 20-200W, 150W LED
Time Delay Range	2, 5, 10, 30, 60, 90, 120, 180 Minutes, User Adjustable (DIP Switch)

Data sheet **DS3HDN**

Permanent ON Facility	No
Multiple Unit Support	No
Cable Entry(s)	x8 M20 Knock Outs Holes Via Back Box

General

Weight (g)	213
Height (mm)	94
Width (mm)	94
Depth (mm)	57
Body Construction	Polycarbonate
Product Colour	Grey
EAN Number	5012483014882
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams



