



Data Sheet

Product Code: HDY3VS.PD

This product can also be made using our Matrix System, using the products WDY1VS.PD + MTP402 x 1

Product Description: 1-Gang 2-Way V-Dim Push On/Off Rotary Dimmer 1 x 60-400W

Range: Screwless

Finish: Primed

Product Category: Halogen Dimmers

Insert/Knob Colour: Polished Brass Knob

Barcode: 5021575997934

Dimensions: 86x86x49mm

Faceplate Depth: 4mm

Net Weight: 156g

Gross Weight: 158g

Fixing Centres: 60.3mm

Depth from Mounting Face:

Recommended Back Box Depth: 35mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Halogen; 400W

Maximum Current Rating: 1.7A

Terminal (Live) Diameter: 3.2mm; **Capacity:** 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; **Capacity:** 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers or electric motors. Do not overload. Product Must Be Earthed.



10 YEAR GUARANTEE

BRITISH MADE 

Product Features

- ☑ V-Dim dimming technology
- ☑ Ideal for incandescent lighting including mains and low voltage halogen
- ☑ Sleek, low-profile screwless faceplate
- ☑ For helpful tips on painting the Varilight Primed range, featuring different paints and methods, see our Varilight Primed - Best Practices article.



Applicable Safety Standard: BS 5518

Commodity Code: 85365007

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 23rd April 2024 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.