



Data Sheet

Product Code: JFCDP254

This product can also be made using our Matrix System, using the products WFCD4 + MJP120 \times 4

Product Description: 4-Gang 2-Way Push-On/Off Rotary LED

Dimmer 4 x 0-120W (1-10 LEDs) (Twin Plate)

Range: Ultraflat

Finish: Polished Chrome

Product Category: V-Pro Dimmer

Insert/Knob Colour: Chrome Knobs

Barcode: 5021575841046

Dimensions: 89x149x47mm

Faceplate Depth: 1mm

Net Weight: 339g

Gross Weight: 342g

Fixing Centres: 120.6mm

Depth from Mounting Face: 25.2mm

Recommended Back Box Depth: 35mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 120W (Max. 10 lamps)

Maximum Current Rating: 0.9A

Terminal (Live) Diameter: 3.2mm; Capacity: 3×1.5 mm²
Terminal (Earth) Diameter: 3.3mm; Capacity: 3×1.5 mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.



Product Features

- V-Pro intelligent dimming technology
- ② Soft start feature and intelligent overload protection
- Adjustable minimum brightness setting and choice of driving modes
- Ocontemporary, ultra-slim faceplate



10 YEAR GUARANTEE



Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.