



Data Sheet Product Code: JRES002



Product Features

- ⊘ V-Pro intelligent dimming technology
- Ø Soft start feature and intelligent overload protection

O Use with touch & remote master Multi-Point dimmers in multi-way circuits

Bevelled edge faceplate



Product Description: 2-Gang Tactile Touch Control Dimming Supplementary Controller for use with Multi-Point (formerly Eclique2) Master on 2-Way Circuits

Range: Classic

Finish: Pewter

Product Category: V-Pro Multi-Point (formerly Eclique2) Dimmer

Insert/Knob Colour: Chrome Buttons

Barcode: 5021575552225

Dimensions: 91x91x27mm

Faceplate Depth: 8mm

Net Weight: 126g

Gross Weight: 128g

Fixing Centres: 60.3mm

Depth from Mounting Face: 16.1mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Refer to Master Dimmer

Maximum Current Rating: Refer to Master Dimmer

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Note: Some LED lamps are not designed for electronic dimmer switches and may remain illuminated even when a dimmer switch is turned off. This can be corrected using one Varilight LEDFix load regulator per circuit (part number YAGF-P). **10 YEAR GUARANTEE**



Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.