



## **Data Sheet**

Product Code: MKP220



② Can be used to replace dimmer modules in existing faceplates or in the Matrix

**⊘** V-Com intelligent TRIAC leading edge dimming technology

❷ Suitable for 1-Gang Single, 1-Gang Twin & 2-Gang Twin Matrix Kits

**⊘** Soft start feature and intelligent overload protection

② Suitable for many dimmable LED lamps

Product Description: 1-Gang 2-Way Push-On/Off Rotary LED Dimmer 1 x 20-220W (Max 26 LEDs) Replacement Module Kit

Range: Module

Finish: Matrix

Product Category: V-Com Module

Barcode: 5021575999907

Dimensions: 50x37x45mm (Click here to see full dimensions)

Net Weight: 48g Gross Weight: 50g Fixing Centres: N/A

Depth from Mounting Face:

Recommended Back Box Depth: N/A

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 220W (Max. 26 LEDs)

Maximum Current Rating: 1A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm<sup>2</sup>

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wirewound or toroidal transformers or electric motors. Do not overload.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

10 YEAR GUARANTEE

**Product Features** 

dimmer grid system



All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.